

Application

Expertly hand crafted glass combined with cost effective and durable technology, this ceiling and wall luminaire offers a broad range of lighting design opportunities. Perfect proportions and impressive glass help this luminaire make a lasting impression.

Materials

Hand-blown three-ply opal glass  
Aluminum housing

NRTL listed to North American Standards, for interior use only

Weight: 11.2lbs.

Electrical



|                           |                                |
|---------------------------|--------------------------------|
| Operating voltage         | 120-277VAC                     |
| Minimum start temperature | -30° C                         |
| LED module wattage        | 25.2 W                         |
| System wattage            | 29.0 W                         |
| Controllability           | 0-10V, TRIAC, and ELV dimmable |
| Color rendering index     | Ra > 90                        |
| Luminaire lumens          | 2206 lm                        |
| LED service life (L70)    | 60000hrs                       |

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Type:  
BEGA Product:  
Project:  
Modified:



| Ceiling and wall luminaire · Opal glass |     |        |        |       |    |
|-----------------------------------------|-----|--------|--------|-------|----|
|                                         |     | LED    | A      | B     | C  |
| B12163                                  | ADA | 25.2 W | 16 1/2 | 3 3/4 | 11 |

