

Application

Designed for low mounting heights for interior and exterior locations, the shielded light distribution is ideal for the glare-free illumination of ground surfaces, building entrances, stairs, and footpaths.

Materials

Clear safety glass with optical texture
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Corrosion-resistant 304 grade stainless steel
High temperature silicone gasket
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 64

Weight: 4.5 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	3.4 W
System wattage	4.9 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	9 lm
LED service life (L70)	60000 hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:

BEGA Product:

Project:

Modified:

Available options

- | | |
|---------------------------------|---------------------------------|
| ☐ AMB | Amber LED |
| ☐ DALI-2 | Enabled for DALI control system |
| ☐ FSC | Fusing |


Available accessories

- | | |
|---------------------------------|---------------------------|
| ☐ B19535 | Concrete protection cover |
|---------------------------------|---------------------------|

See individual accessory spec sheet for details.

Included (available for pre-shipment)

- | | |
|------------------------------------|----------------------|
| ☐ BB2033LED | Installation housing |
|------------------------------------|----------------------|



Recessed wall luminaire · Shielded					
		LED	A	B	C
B22135	ADA	3.4 W	7 1/2	3 1/8	4

