

Application

As individual luminaires with low mounting height, they can be used for marking danger areas or in rows for illuminating corridors and passageways. With high mounting heights they can be used as wall luminaires next to doors or for lighting small wall areas.

Materials

Clear safety glass with matte finish
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Mechanically captive stainless steel fasteners
Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 64

Weight: 0.9 lbs.

Electrical

Operating voltage 120-277VAC
Minimum start temperature -20° C
LED module wattage 2.1 W
System wattage 3.0 W
Controllability Non-Dimming
Color rendering index Ra > 90
Luminaire lumens 173 lm
LED service life (L70) 60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- Natural Bronze (NTB)
- CUS:
- Bronze (BRZ)
- White (WHT)
- RAL:

Type:

BEGA Product:

Project:


Modified:

Available options

- CUS Custom finish
- FSC Fusing
- MGU Marine grade undercoat
- NTB Natural bronze (premium finish)
- RAL RAL Classic, matte finish

Included (available for pre-shipment)

- B19538 Small opening wiring box



Wall luminaire · Directed light				
	LED	A	B	C
B22215	ADA 2.1 W	3 1/2	3 3/4	2 3/8

