

Application

Designed for low mounting heights for interior and exterior locations, the asymmetric distribution provides light in a forward orientation and is suitable for lighting ground surfaces, building entrances, and stairways.

Materials

- Clear safety glass
- Die-cast aluminum
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Stainless steel screw clamps
- Aluminum installation housing
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 0.6 lbs.

Electrical

- Operating voltage24VDC (remote power supply req.)
- Minimum start temperature-40° C
- LED module wattage2.1 W
- System wattage3.1 W
- ControllabilityNon-Dimming
- Color rendering indexRa > 80
- Luminaire lumens43 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- Natural Bronze (NTB)
- CUS:
- Bronze (BRZ)
- White (WHT)
- RAL:

Type:

BEGA Product:

Project:

Modified:

Available options

- CUSCustom finish
- MGUMarine grade undercoat
- NTBNatural bronze (premium finish)
- RALRAL Classic, matte finish


Available accessories

- B19580Remote driver box · Static white
- B19591Remote driver box · Static white

See individual accessory spec sheet for details.

Included (available for pre-shipment)

- BB2002LEDInstallation housing



Recessed wall luminaire · Directed light · 24V DC				
		LED	A	B
B22230	ADA	2.1 W	3 1/8	4

