

Application

This wall mounted luminaire has light output in two directions. Arranged individually or in groups, it is a great design element for a host of lighting applications.

Materials

Clear safety glass with matte finish
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 4.2 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	15.4 W
System wattage	20.5 W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 80
Luminaire lumens	1663 lm
LED service life (L70)	60000 hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- | | |
|---|---------------------------------------|
| ☐ Black (BLK) | ☐ Bronze (BRZ) |
| ☐ Silver (SLV) | ☐ White (WHT) |
| ☐ Natural Bronze (NTB) | ☐ RAL: |
| ☐ CUS: | |

Type:


BEGA Product:

Project:

Modified:

Available options

- | | |
|------------------------------|---------------------------------|
| ☐ AMB | Amber LED |
| ☐ CUS | Custom finish |
| ☐ MGU | Marine grade undercoat |
| ☐ NTB | Natural bronze (premium finish) |
| ☐ RAL | RAL Classic, matte finish |



Wall luminaire · Light emission on two sides

		LED	A	B	C
B22365	ADA	15.4 W	12 1/2	4 3/8	4

