

Application

This luminaire can be utilized at low or high mounting heights to illuminate pathways and corridors for safety and egress purposes.

Materials

- Clear safety glass with matte finish
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 2.1 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage6.1 W
- System wattage9.0W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens407 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- | | |
|----------------------|--------------|
| Black (BLK) | Bronze (BRZ) |
| Silver (SLV) | White (WHT) |
| Natural Bronze (NTB) | RAL: |
| CUS: | |

Type:


BEGA Product:

Project:

Modified:

Available options

- | | |
|--------|---------------------------------|
| CUS | Custom finish |
| DALI-2 | Enabled for DALI control system |
| MGU | Marine grade undercoat |
| NTB | Natural bronze (premium finish) |
| RAL | RAL Classic, matte finish |



Wall luminaire · Directed light

		LED	A	B	C
B22375	ADA	6.1 W	7 ⁷ / ₈	4 ³ / ₄	3

