

Application

This wall luminaire with an asymmetric light distribution can be used to illuminate ceiling or ground surfaces in front of the mounting surface. Able to be installed in either direction for uplight or downlight applications.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Silicone applied robotically to casting, plasma treated for increased adhesion
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 6.8 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage17.9 W
- System wattage23.0 W
- Controllability0-10V dimming down to 1%
- Color rendering indexRa > 90
- Luminaire lumens2352 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.


Available colors

- Black (BLK)
 - Silver (SLV)
 - Natural Bronze (NTB)
 - CUS:
- Bronze (BRZ)
 - White (WHT)
 - RAL:

Type:
BEGA Product:
Project:
Modified:

Available options

- CUS
 - FSC
 - MGU
 - NTB
 - RAL
- Custom finish
 - Fusing
 - Marine grade undercoat
 - Natural bronze (premium finish)
 - RAL Classic, matte finish



Wall washer · Asymmetric				
	LED	A	B	C
B22386	17.9 W	9 1/2	4 1/8	7 7/8

