

Application

Designed for indirect or direct lighting effects for interior and exterior locations. This wall luminaire is for illuminating wall surfaces, with the mounting surface also acting as the reflection surface. DarkSky Approved when installed facing down (2700K and 3000K only)

Materials

- Clear safety glass with white ceramic coating
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Galvanized zinc-plated mounting bracket
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 4.9 lbs.

Electrical

- Operating voltage120, 220-240 OR 277 VAC
- Minimum start temperature-30° C
- LED module wattage17.9 W
- System wattage21.0 W
- Controllability0-10V dimmable
- Color rendering indexRa > 90
- Luminaire lumens2030 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3) (DarkSky Approved)
- 2700K (K27) (DarkSky Approved)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)

Silver (SLV)

Natural Bronze (NTB)

CUS:
- Bronze (BRZ)

White (WHT)

RAL:

Type:
BEGA Product:
Project:
Modified:

Available options

- CUS

MGU

NTB

RAL
- Custom finish


Marine grade undercoat

Natural bronze (premium finish)

RAL Classic, matte finish

Included (available for pre-shipment)

- B19538
- Small opening wiring box



Wall washer · Symmetric				
	LED	A	B	C
B22449	17.9 W	6 1/2	6 5/8	7 1/8

