

Application

The material thickness and strong crystal glass makes this impact-resistant luminaire extremely robust. Arranged individually or in groups, they are great design elements for a host of lighting applications.

Materials

- Pressed crystal glass with white ceramic coating on one side
- Die-cast aluminum
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 4.5 lbs.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-30° C
- LED module wattage11.8W
- System wattage15.0W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens1220lm
- LED service life (L70)60000hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- ☐ Black (BLK)
- ☐ Bronze (BRZ)
- ☐ Silver (SLV)
- ☐ White (WHT)
- ☐ Natural Bronze (NTB)
- ☐ RAL:
- ☐ CUS:

Type:

BEGA Product:

Project:

Modified:

Available options

- ☐ CUSCustom finish
- ☐ MGUMarine grade undercoat
- ☐ NTBNatural bronze (premium finish)
- ☐ RALRAL Classic, matte finish



Impact-resistant ceiling and wall luminaire · Unshielded				
		LED	A	B
B22470	ADA	11.8 W	10 1/4	4