

Application

Impact-resistant ceiling and wall luminaire with unshielded light distribution and safety guard. Arranged individually or in groups, they are great design elements for a host of lighting applications.

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 1.8 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	4.2W
System wattage	4.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	248lm
LED service life (L70)	60000hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- ☐ Black (BLK)

☐ Bronze (BRZ)
- ☐ Silver (SLV)

☐ White (WHT)
- ☐ Natural Bronze (NTB)

☐ RAL:
- ☐ CUS:

Type:

BEGA Product:

Project:

Modified:


Available options

- ☐ CUS

Custom finish
- ☐ MGU

Marine grade undercoat
- ☐ RAL

RAL Classic, matte finish



Impact-resistant ceiling and wall luminaire · Polycarbonate

		LED	A	B	C
B22862	ADA	4.2 W	8 ³ / ₄	5 ¹ / ₈	3 ⁷ / ₈

