

Application

Impact-resistant ceiling and wall luminaire with unshielded light distribution and safety guard. Arranged individually or in groups, they are great design elements for a host of lighting applications.

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 3.1 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	3.9W
System wattage	6.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	417 lm
LED service life (L70)	60000hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- ☐ Black (BLK)
- ☐ Bronze (BRZ)
- ☐ Silver (SLV)
- ☐ White (WHT)
- ☐ Natural Bronze (NTB)
- ☐ RAL:
- ☐ CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

- ☐ CUS
- Custom finish
- ☐ MGU
- Marine grade undercoat
- ☐ RAL
- RAL Classic, matte finish



Impact-resistant ceiling and wall luminaire · Polycarbonate

	LED	A	B	C
B22864	3.9W	11 ⁷ / ₈	7 ¹ / ₈	5 ¹ / ₂

