

**Application**  
Expertly hand crafted glass combined with cost effective and durable technology, this ceiling and wall luminaire offers a broad range of lighting design opportunities. Perfect proportions and impressive glass help this luminaire make a lasting impression.

**Materials**  
Hand-blown three-ply opal glass  
Aluminum housing

**NRTL** listed to North American Standards, for interior use only

**Weight:** 7.3 lbs.

**Electrical**


|                           |                |
|---------------------------|----------------|
| Operating voltage         | 120-277VAC     |
| Minimum start temperature | -30° C         |
| LED module wattage        | 17.8 W         |
| System wattage            | 21.8 W         |
| Controllability           | 0-10V dimmable |
| Color rendering index     | Ra > 80        |
| Luminaire lumens          | 2175 lm        |
| LED service life (L70)    | 60000 hrs      |

**LED color temperature**

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Type:  
BEGA Product:  
Project:  
Modified:



| Ceiling and wall luminaire · Opal glass |     |        |                                |                               |    |
|-----------------------------------------|-----|--------|--------------------------------|-------------------------------|----|
|                                         |     | LED    | A                              | B                             | C  |
| B23414                                  | ADA | 17.8 W | 16 <sup>5</sup> / <sub>8</sub> | 3 <sup>3</sup> / <sub>4</sub> | 11 |