

Wall luminaire · Narrow beam upward · Narrow beam downward

BEGA

Application

Wall luminaires with directed narrow beam light distribution on two sides. Arranged individually or in groups, they are great design elements for a host of lighting applications.

Materials

Clear safety glass  
Marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners  
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 6.6 lbs.

Electrical

|                           |                |
|---------------------------|----------------|
| Operating voltage         | 120-277V AC    |
| Minimum start temperature | -30° C         |
| LED module wattage        | 24.2 W         |
| System wattage            | 28.0 W         |
| Controllability           | 0-10V dimmable |
| Color rendering index     | Ra > 80        |
| Luminaire lumens          | 2235 lm        |
| LED service life (L70)    | 60000 hrs      |

LED color temperature

4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

|                      |              |
|----------------------|--------------|
| Black (BLK)          | Bronze (BRZ) |
| Silver (SLV)         | White (WHT)  |
| Natural Bronze (NTB) | RAL:         |
| CUS:                 |              |

Type:

BEGA Product:

Project:

Modified:

Available options

|     |                                 |
|-----|---------------------------------|
| CUS | Custom finish                   |
| FSC | Fusing                          |
| MGU | Marine grade undercoat          |
| NTB | Natural bronze (premium finish) |
| RAL | RAL Classic, matte finish       |

Available accessories

B79547 Surface mounted wiring box

See individual accessory spec sheet for details.

Included (available for pre-shipment)

B19537 Narrow opening wiring box



Wall luminaire · Narrow beam upward · Narrow beam downward

|        | LED    | $\beta$ | A                             | B                              | C                             | D                             |
|--------|--------|---------|-------------------------------|--------------------------------|-------------------------------|-------------------------------|
| B24008 | 24.2 W | 18°     | 4 <sup>3</sup> / <sub>8</sub> | 19 <sup>5</sup> / <sub>8</sub> | 6 <sup>3</sup> / <sub>8</sub> | 1 <sup>5</sup> / <sub>8</sub> |



BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com  
© copyright BEGA 2026 Updated 08/21/26