

Application
Ceiling and wall luminaire with hand-blown, satin matte opal glass for a soft and uniform light distribution. Some of the light exits behind the shield and also illuminates the mounting surface.

Materials
Hand-blown opal glass
Three-ply opal glass with satin matte finish
A380 aluminum alloy
Stainless steel housing
High temperature silicone gasket
Stainless steel mounting plate
NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 3.97 lbs.

Electrical
Operating voltage 120-277VAC
Minimum start temperature -40° C
Maximum ambient temperature 50° C
LED module wattage 8.0W
System wattage 10.0W
Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 1022 lm
LED service life (L70) 60000 hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors
Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
Natural Bronze (NTB) RAL:
CUS:

Type:
BEGA Product:
Project:
Modified:

Available options
CUS Custom finish
FSC Fusing
MGU Marine grade undercoat
NTB Natural bronze (premium finish)
RAL RAL Classic, matte finish



Ceiling and wall luminaire · Opal glass					
		LED	A	B	C
B24042	ADA	8.0W	10 ⁵ / ₈	2 ⁷ / ₈	8

