

Application

Designed for accent lighting of walls and facades. A variety of beam angles produce a striking pattern on the installation surface in any orientation.

Materials

- Borosilicate glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Silicone applied robotically to casting, plasma treated for increased adhesion
- Mechanically captive stainless steel fasteners
- High temperature silicone gasket
- Galvanized zinc-plated mounting bracket
- Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 4.0 lbs.

Electrical

- Operating voltage 120-277V AC
- Minimum start temperature -30° C
- LED module wattage 17.0 W
- System wattage 21.0 W
- Controllability 0-10V, TRIAC, and ELV dimmable
- Color rendering index Ra > 80
- Luminaire lumens 717 lm
- LED service life (L70) 60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- | | |
|----------------------|--------------|
| Black (BLK) | Bronze (BRZ) |
| Silver (SLV) | White (WHT) |
| Natural Bronze (NTB) | RAL: |
| CUS: | |

Type:


BEGA Product:

Project:

Modified:

Available options

- NTB Natural bronze (premium finish)



Wall luminaire · Three 90° ports · One 15° port				
		LED	A	B
B24046	ADA	17.0 W	7 1/8	2 7/8