

Application
Designed for accent lighting of walls and facades by creating striking lighting effects on the installation surface. These luminaires may be mounted in any orientation to create interesting designs by utilizing multiple luminaires.

Materials
Borosilicate glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Silicone applied robotically to casting, plasma treated for increased adhesion
Mechanically captive stainless steel fasteners
High temperature silicone gasket
Galvanized zinc-plated mounting bracket
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 4.4 lbs.

Electrical
Operating voltage 120-277V AC
Minimum start temperature -30° C
LED module wattage 9.5W
System wattage 12.0W
Controllability 0-10V, TRIAC, and ELV dimmable
Color rendering index Ra > 80
Luminaire lumens 239lm
LED service life (L70) 60000 hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors
Black (BLK) Silver (SLV)
Natural Bronze (NTB) Bronze (BRZ)
White (WHT) RAL:
CUS:

Type:
BEGA Product:
Project:
Modified:

Available options
CUS Custom finish
DALI-2 Enabled for DALI control system
FSC Fusing
MGU Marine grade undercoat
NTB Natural bronze (premium finish)
RAL RAL Classic, matte finish



Wall luminaire · One 90° port · One 15° port				
		LED	A	B
B24049	ADA	9.5W	7 1/2	3 1/8