

Application

Recessed wall luminaire with directed light distribution for the illumination of ground surfaces, building entrances, plazas, and footpaths from a low mounting height.

Materials

- Clear safety glass with optical texture
- Corrosion-resistant 304 grade stainless steel
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Aluminum installation housing

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 67

Weight: 10.2 lbs.

Electrical

- | | |
|---------------------------|--------------------------------|
| Operating voltage | 120-277V AC |
| Minimum start temperature | -30° C |
| LED module wattage | 13.5 W |
| System wattage | 16.0 W |
| Controllability | 0-10V, TRIAC, and ELV dimmable |
| Color rendering index | Ra > 80 |
| Luminaire lumens | 1211 lm |
| LED service life (L70) | 60000 hrs |

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:
BEGA Product:
Project:
Modified:

Available options

- ☐ FSC
- Fusing

Included (available for pre-shipment)

- ☐ BB24104
- Installation housing



Recessed wall luminaire · Directed light				
	LED	A	B	C
B24107	13.5 W	25 ³ / ₈	5	5

