

Application

Recessed wall luminaire with directed light distribution for the illumination of ground surfaces, building entrances, plazas, and footpaths from a low mounting height.

Materials

- Clear safety glass with optical texture
- Corrosion-resistant 304 grade stainless steel
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Aluminum installation housing

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 67

Weight: 23.2 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage39.2 W
- System wattage45.0 W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens3410 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:
BEGA Product:
Project:
Modified:

Available options
FSC Fusing

Included (available for pre-shipment)
BB24106 Installation housing



Recessed wall luminaire · Directed light				
	LED	A	B	C
B24109	39.2 W	60 ⁷ / ₈	5	5

