

Application

A ceiling and wall luminaire offering quality illumination with maximum visual comfort. Arranged individually as bands of light, or in groups, this luminaire is an effective design element.

Materials

- White UV-stabilized acrylic diffuser
- Extruded aluminum
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 23.3lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-20° C
- LED module wattage44.4 W
- System wattage58.0 W
- Controllability0-10V dimming down to 0.1%
- Color rendering indexRa > 80
- Luminaire lumens7712lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)Bronze (BRZ)
- Silver (SLV)White (WHT)
- Natural Bronze (NTB)RAL:
- CUS:

Type:

BEGA Product:

Project:

Modified:

Available options

- CUSCustom finish
- DALI-2Enabled for DALI control system
- MGUMarine grade undercoat
- NTBNatural bronze (premium finish)
- RALRAL Classic, matte finish



Ceiling and wall luminaire · Unshielded

	LED	A	B	C
B24117	44.4 W	72 ¹ / ₄	4 ⁷ / ₈	4 ⁵ / ₈

