

Application

Wall washer with light output in one direction. This luminaire is ideally suited for the even illumination of vertical mounting surfaces. Arranged individually or in groups, they are a great design element for a host of lighting applications.

Materials

- Clear safety glass with optical texture
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Silicone applied robotically to casting, plasma treated for increased adhesion
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Galvanized zinc-plated mounting bracket
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 64

Weight: 7.1 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage16.8 W
- System wattage21.0 W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens1083 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- Natural Bronze (NTB)
- CUS:
- Bronze (BRZ)
- White (WHT)
- RAL:

Type:


BEGA Product:

Project:

Modified:

Available options

- CUSCustom finish
- MGUMarine grade undercoat
- NTBNatural bronze (premium finish)
- RALRAL Classic, matte finish



Wall washer · Light emission on one side				
	LED	A	B	C
B24134	16.8 W	7	7	6 7/8

