

Application

Large-scale round luminaire designed to provide high-output diffuse illumination over very large areas such as lobbies, atriums, and other interior and exterior spaces.

Materials

White high-density polyethylene diffuser
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 39.0lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-40° C
LED module wattage	117.6W
System wattage	133.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	13105lm
LED service life (L70)	60000hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:


BEGA Product:

Project:

Modified:

Available options

CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL Classic, matte finish



Large-area ceiling and wall luminaire · Unshielded			
	LED	A	B
B24231	117.6W	36 ⁵ / ₈	5 ¹ / ₂

