

Application

Wall mount luminaire with asymmetric light distribution designed for the illumination of parking areas and roadways.

Materials

- Clear safety glass with optical texture
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High-strength A572 stainless steel alloy
- High temperature silicone gasket
- Integral surge protector
- Stainless steel mounting plate
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 66

Weight: 9.5 lbs.

EPA (Effective projection area): 0.32 sq. ft.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-30° C
- Maximum ambient temperature90° C
- LED module wattage12.6W
- System wattage17.0W
- Controllability0-10V, TRIAC, and ELV dimmable
- Color rendering indexRa > 80
- Luminaire lumens2063 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- |                      |              |
|----------------------|--------------|
| Black (BLK)          | Bronze (BRZ) |
| Silver (SLV)         | White (WHT)  |
| Natural Bronze (NTB) | RAL:         |
| CUS:                 |              |



Area/roadway wall luminaire · Asymmetric

|        | LED   | A  | B                             | C                              | D                             |
|--------|-------|----|-------------------------------|--------------------------------|-------------------------------|
| B24350 | 12.6W | 10 | 2 <sup>3</sup> / <sub>8</sub> | 16 <sup>1</sup> / <sub>8</sub> | 5 <sup>1</sup> / <sub>4</sub> |

Type:

BEGA Product:

Project:

Modified:

Available options

- |        |                                                    |
|--------|----------------------------------------------------|
| AMB    | Amber LED                                          |
| CUS    | Custom finish                                      |
| DALI-2 | Enabled for DALI control system                    |
| FSC    | Fusing                                             |
| IMS-L2 | Integral motion sensor (48' ⌘ coverage at 8' AFG)  |
| IMS-L3 | Integral motion sensor (40' ⌘ coverage at 20' AFG) |
| MGU    | Marine grade undercoat                             |
| NTB    | Natural bronze (premium finish)                    |
| RAL    | RAL Classic, matte finish                          |

Available accessories

- BFSIR-100 Handheld configuration tool
- See individual accessory spec sheet for details.

