

**Application**  
A robust and timeless wall luminaire for a host of lighting applications. Fasteners are not visible on the front of the housing adding to the elegance of this design.

**Materials**  
Pressed crystal glass with white ceramic coating on one side  
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy  
High temperature silicone gasket  
Galvanized zinc-plated mounting bracket

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 65

**Weight:** 2.9 lbs.

|                           |                |
|---------------------------|----------------|
| <b>Electrical</b>         |                |
| Operating voltage         | 120-277VAC     |
| Minimum start temperature | -30° C         |
| LED module wattage        | 3.0W           |
| System wattage            | 6.2W           |
| Controllability           | 0-10V dimmable |
| Color rendering index     | Ra > 80        |
| Luminaire lumens          | 214 lm         |
| LED service life (L70)    | 60000hrs       |

**LED color temperature**  
4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)


**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**  
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

|                         |              |
|-------------------------|--------------|
| <b>Available colors</b> |              |
| Black (BLK)             | Bronze (BRZ) |
| Silver (SLV)            | White (WHT)  |
| Natural Bronze (NTB)    | RAL:         |
| CUS:                    |              |

Type:  
BEGA Product:  
Project:  
Modified:

|                          |                                 |
|--------------------------|---------------------------------|
| <b>Available options</b> |                                 |
| CUS                      | Custom finish                   |
| DALI-2                   | Enabled for DALI control system |
| MGU                      | Marine grade undercoat          |
| NTB                      | Natural bronze (premium finish) |
| RAL                      | RAL Classic, matte finish       |



| Wall luminaire · Shielded · Crystal glass |            |      |                               |                               |                               |
|-------------------------------------------|------------|------|-------------------------------|-------------------------------|-------------------------------|
|                                           |            | LED  | A                             | B                             | C                             |
| <b>B24355</b>                             | <b>ADA</b> | 3.0W | 8 <sup>5</sup> / <sub>8</sub> | 4 <sup>3</sup> / <sub>4</sub> | 3 <sup>1</sup> / <sub>4</sub> |

