

Application

Designed for indirect or direct lighting effects for interior and exterior locations. This wall luminaire is for illuminating surfaces adjacent to the installation surface, such as ceilings, arches, and canopies.

Materials

- Clear safety glass
- Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Silicone applied robotically to casting, plasma treated for increased adhesion
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 5.8 lbs.

Electrical

Operating voltage	120, 220-240 OR 277 VAC
Minimum start temperature	-30° C
LED module wattage	33.6 W
System wattage	38.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	3712 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:


BEGA Product:

Project:

Modified:

Available options

CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL Classic, matte finish



Wall washer · Asymmetric				
	LED	A	B	C
B24362	33.6 W	12 ⁵ / ₈	4 ¹ / ₄	6

