

Application

Compact ceiling mounted downlights designed for down lighting atriums, canopies, passages and other interior and exterior locations.

Materials

Clear safety glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Silicone applied robotically to casting, plasma treated for increased adhesion
Pure anodized aluminum reflector surface
Silicone optic with excellent high temperature and UV stability
BEGA Hybrid Optics®

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 1.65lbs.

Electrical

Operating voltage120-277VAC
Minimum start temperature-30° C
LED module wattage8.0W
System wattage12.0W
Controllability0-10V dimmable
Color rendering indexRa > 80
Luminaire lumens961 lm
LED service life (L70)60000hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)Bronze (BRZ)
Silver (SLV)White (WHT)
RAL:CUS:

Type:

BEGA Product:

Project:


Modified:

Available options

CUSCustom finish
DALI-2Enabled for DALI control system
FSCFusing
MGUMarine grade undercoat
RALRAL Classic, matte finish

Included (available for pre-shipment)

B19538Small opening wiring box



Surface mounted downlight · Symmetric very wide beam

	LED	β	A	B
B24409	8.0W	55°	3 ⁷ / ₈	4 ³ / ₈

