

Application

Pendant luminaire with symmetric wide beam light distribution and clear synthetic diffuser. This luminaire creates vertical illumination in addition to the downward light ideal for high activity spaces.

Materials

- Clear UV-stabilized acrylic diffuser
- Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Stainless steel suspension cable
- Galvanized zinc-plated mounting bracket
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 15.5 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-40° C
- LED module wattage35.7 W
- System wattage40.0 W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens4519 lm
- LED service life (L70)60000 hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- ☐ Black (BLK)
- ☐ Silver (SLV)
- ☐ Natural Bronze (NTB)
- ☐ CUS:
- ☐ Bronze (BRZ)
- ☐ White (WHT)
- ☐ RAL:

Type:

BEGA Product:

Project:

Modified:

Available options

- ☐ CUSCustom finish
- ☐ MGUMarine grade undercoat
- ☐ NTBNatural bronze (premium finish)
- ☐ RALRAL Classic, matte finish


Available accessories

- ☐ B70477Cable hanger

See individual accessory spec sheet for details.

Included (available for pre-shipment)

- ☐ B19538Small opening wiring box



Pendant · Unshielded				
	LED	A	B	C
B24508	35.7 W	7 1/2	38 3/4	125 1/4

