

Application

Designed for accent lighting of columns, walls, and facades. The unique distributions in each direction produce an interesting pattern of light on the installation surface. The symmetric very wide beam distribution is ideal for general illumination of pathways and corridors, while the narrow beam distribution highlights architectural features.

Materials

Clear safety glass with matte finish  
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy  
Silicone applied robotically to casting, plasma treated for increased adhesion  
Stainless steel mounting plate  
Pure anodized aluminum reflector surface

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 8.4 lbs.

Electrical

Operating voltage 120-277VAC  
Minimum start temperature -30° C  
Maximum ambient temperature 40° C  
LED module wattage 35.4W  
System wattage 41.0W  
Controllability 0-10V, TRIAC, and ELV dimmable  
Color rendering index Ra > 90  
Luminaire lumens 3166 lm  
LED service life (L70) 60000 hrs

LED color temperature

4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)  
Silver (SLV) White (WHT)  
Natural Bronze (NTB) RAL:  
CUS:

Type:

BEGA Product:

Project:


Modified:

Available options

CUS Custom finish  
DALI-2 Enabled for DALI control system  
FSC Fusing  
MGU Marine grade undercoat  
NTB Natural bronze (premium finish)  
RAL RAL Classic, matte finish

Included (available for pre-shipment)

B19542 Narrow opening wiring box



Wall luminaire · Narrow beam · Very wide beam

|        | LED    | β       | A                             | B                             | C                             |
|--------|--------|---------|-------------------------------|-------------------------------|-------------------------------|
| B24516 | 35.4 W | 14°/70° | 5 <sup>3</sup> / <sub>4</sub> | 9 <sup>1</sup> / <sub>4</sub> | 7 <sup>1</sup> / <sub>2</sub> |

