

Application

Recessed wall luminaire with directed light distribution for the illumination of ground surfaces, stairs and pathways.

Materials

- Clear safety glass with optical texture
- BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Mechanically captive stainless steel fasteners
- Stainless steel screw clamps
- Stainless steel helicoils
- High temperature silicone gasket
- Silicone applied robotically to casting, plasma treated for increased adhesion
- Composite installation housing

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 7.3 lbs.

Electrical

- Operating voltage120V or 277V AC
- Minimum start temperature-30° C
- LED module wattage20.0W
- System wattage27.0W
- Controllability0-10V, TRIAC, and ELV dimmable
- Color rendering indexRa > 80
- Luminaire lumens2626 lm
- LED service life (L70)60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- Natural Bronze (NTB)
- CUS:
- Bronze (BRZ)
- White (WHT)
- RAL:

Type:

BEGA Product:

Project:


Modified:

Available options

- CUSCustom finish
- DALI-2Enabled for DALI control system
- EMPKIntegral emergency battery pack (30% output for 90 minutes)
- FSCFusing
- MGUMarine grade undercoat
- NTBNatural bronze (premium finish)
- RALRAL Classic, matte finish

Included (available for pre-shipment)

- BB24573Installation housing



| Recessed wall luminaire · Directed light |            |        |        |       |
|------------------------------------------|------------|--------|--------|-------|
|                                          | LED        | A      | B      | C     |
| B24574                                   | ADA 20.0 W | 11 3/4 | 11 3/4 | 5 1/4 |