

Application

Recessed wall luminaire with forward throw light distribution for the illumination of ground surfaces, stairs and pathways.

Materials

- Clear safety glass with optical texture
- BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Mechanically captive stainless steel fasteners
- Stainless steel helicoils
- Stainless steel screw clamps
- High temperature silicone gasket
- Silicone applied robotically to casting, plasma treated for increased adhesion
- Composite installation housing

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 7.3 lbs.

Electrical

- Operating voltage120V or 277V AC
- Minimum start temperature-30° C
- LED module wattage20.0W
- System wattage27.0W
- Controllability0-10V, TRIAC, and ELV dimmable
- Color rendering indexRa > 80
- Luminaire lumens2255lm
- LED service life (L70)60000hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- ☐ Black (BLK)
- ☐ Silver (SLV)
- ☐ Natural Bronze (NTB)
- ☐ CUS:
- ☐ Bronze (BRZ)
- ☐ White (WHT)
- ☐ RAL:

Type:

BEGA Product:

Project:


Modified:

Available options

- ☐ CUSCustom finish
- ☐ DALI-2Enabled for DALI control system
- ☐ EMPKIntegral emergency battery pack (30% output for 90 minutes)
- ☐ FSCFusing
- ☐ MGUMarine grade undercoat
- ☐ NTBNatural bronze (premium finish)
- ☐ RALRAL Classic, matte finish

Included (available for pre-shipment)

- ☐ BB24573Installation housing



Recessed wall luminaire · Asymmetric				
	LED	A	B	C
B24575	ADA 20.0 W	11 3/4	11 3/4	5 1/8

