

Application

An LED wall mounted luminaire with light emission from one side and a symmetrical distribution. Can be arranged individually or in groups to serve a broad range of lighting applications.

Materials

Clear safety glass with optical texture
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Silicone applied robotically to casting, plasma treated for increased adhesion
Stainless steel hardware
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 13.2lbs.

Electrical

Operating voltage 120-277VAC
Minimum start temperature -20° C
LED module wattage 23.2 W
System wattage 28.0 W
Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 2257 lm
LED service life (L70) 60000hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Natural Bronze (NTB) White (WHT)
Silver (SLV) RAL:
CUS:

Type:

BEGA Product:

Project:

Modified:

Available options

CUS Custom finish
DALI-2 Enabled for DALI control system
ELV/TRIAC Electronic low voltage/TRIAC dimming
FSC Fusing
MGU Marine grade undercoat
NTB Natural bronze (premium finish)
RAL RAL Classic, matte finish



Wall luminaire · Light emission on one side · symmetrical

	LED	A	B	C
B24585	23.2 W	24 ⁷ / ₈	4 ¹ / ₈	4 ¹ / ₄

