

Application

Wall mounted luminaire with light emission from one side and an asymmetrical distribution. Can be arranged individually or in groups to serve a broad range of lighting applications.

Materials

Clear safety glass with optical texture  
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
Silicone applied robotically to casting, plasma treated for increased adhesion  
Stainless steel hardware  
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 19.0lbs.

Electrical

Operating voltage 120-277VAC  
Minimum start temperature -20° C  
LED module wattage 34.8W  
System wattage 41.0W  
Controllability 0-10V dimming down to 1%  
Color rendering index Ra > 80  
Luminaire lumens 4358lm  
LED service life (L70) 60000hrs

LED color temperature

4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)  
Natural Bronze (NTB) Silver (SLV)  
White (WHT) RAL:  
CUS:

Type:

BEGA Product:

Project:

Modified:

Available options

CUS Custom finish  
DALI-2 Enabled for DALI control system  
ELV/TRIAC Electronic low voltage/TRIAC dimming  
FSC Fusing  
MGU Marine grade undercoat  
NTB Natural bronze (premium finish)  
RAL RAL Classic, matte finish



| Wall luminaire · Light emission on one side · asymmetrical |       |                                |                               |                               |
|------------------------------------------------------------|-------|--------------------------------|-------------------------------|-------------------------------|
|                                                            | LED   | A                              | B                             | C                             |
| B24641                                                     | 34.8W | 36 <sup>5</sup> / <sub>8</sub> | 4 <sup>1</sup> / <sub>8</sub> | 4 <sup>1</sup> / <sub>4</sub> |

