

Application

A ceiling and wall luminaire with copper and opal glass. Backlight onto the wall or ceiling surface creates a contrast between the opal glass, the shield, and the mounting surface when illuminated.

Materials

Three-ply opal glass with satin matte finish
A380 aluminum alloy
99.9% pure copper
High temperature silicone gasket
Stainless steel mounting plate

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 10.8lbs.

Electrical

Operating voltage 120-277VAC
Minimum start temperature -30° C
Maximum ambient temperature 45° C
LED module wattage 28.1 W
System wattage 33.0 W
Controllability 0-10V dimming down to 1%
Color rendering index Ra > 80
Luminaire lumens 2685 lm
LED service life (L70) 60000hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Natural copper. Time and weather factors will create the natural patina of copper.

Type:


BEGA Product:

Project:

Modified:

Available options

DALI-2 Enabled for DALI control system
ELV/TRIAC Electronic low voltage/TRIAC
FSC Fusing



Ceiling and wall luminaire · Opal glass

	LED	A	B	C
B31043	28.1 W	15 ³ / ₈	4 ¹ / ₈	11 ³ / ₄

