

Application

Wall luminaires with unshielded light distribution. These luminaires are ideally suited for illuminating entrances, arcades and walkways.

Materials

Hand-blown three-ply opal glass
Aluminum housing
Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 44

Weight: 7.7 lbs.

Electrical

Operating voltage 120-277VAC
Minimum start temperature -30° C
LED module wattage 22.0W
System wattage 25.5W
Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 1585lm
LED service life (L70) 60000hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors


Black (BLK)

Type:

BEGA Product:

Project:

Modified:



Wall luminaire · Unshielded				
	LED	A	B	C
B31075	22.0W	4 1/4	25 3/8	6 1/2

