

Application

Wall luminaires with partially shielded light distribution. A combination of materials in perfect harmony with this classic luminaire shape. Whether as single luminaires or arranged in groups, these luminaires are perfect architectural elements.

Materials

Hand-blown three-ply opal glass
99.9% pure copper
High-strength, free machining C38500 brass
Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 44

Weight: 6.4 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	5.3W
System wattage	7.2W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	268lm
LED service life (L70)	60000 hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Natural cast bronze and copper. Time and weather factors will create the natural patina of bronze and copper.

Type:


BEGA Product:

Project:

Modified:

Available options

- ☐ DALI-2 Enabled for DALI control system



Cast bronze and copper wall luminaire · Unshielded

	LED	A	B	C	D
B31086	5.3W	13 ³ / ₄	16	15 ¹ / ₈	4 ³ / ₈

