

Application

Wall luminaires with unshielded light distribution. These luminaires are ideally suited for illuminating entrances, arcades and walkways. Clear-cut lines and high-quality materials result in elements of architectural design that are both striking and long lasting.

Materials

Hand-blown three-ply opal glass
99.9% pure copper
High-strength, free machining C38500 brass
Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 44

Weight: 4.4 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	5.3W
System wattage	7.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	322lm
LED service life (L70)	60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Natural copper with brass. Time and weather factors will create the natural patina of copper.

Type:


BEGA Product:

Project:

Modified:

Available options

DALI-2 Enabled for DALI control system



Copper and brass wall luminaire · Unshielded

	LED	A	B	C	D
B31094	5.3W	3 1/4	16 1/8	5 1/8	3 1/8

