

Application

Wall luminaires with unshielded light distribution. These luminaires are ideally suited for illuminating entrances, arcades and walkways. Clear-cut lines and high-quality materials result in elements of architectural design that are both striking and long lasting.

Materials

Hand-blown three-ply opal glass  
99.9% pure copper  
High-strength, free machining C38500 brass  
Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 44

Weight: 11.0 lbs.

Electrical

|                           |                |
|---------------------------|----------------|
| Operating voltage         | 120-277V AC    |
| Minimum start temperature | -30° C         |
| LED module wattage        | 22.0 W         |
| System wattage            | 25.5 W         |
| Controllability           | 0-10V dimmable |
| Color rendering index     | Ra > 80        |
| Luminaire lumens          | 1540 lm        |
| LED service life (L70)    | 60000 hrs      |

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish


Natural copper with brass. Time and weather factors will create the natural patina of copper.

Type:

BEGA Product:

Project:

Modified:



| Copper and brass wall luminaire · Unshielded |        |       |        |       |
|----------------------------------------------|--------|-------|--------|-------|
|                                              | LED    | A     | B      | C     |
| B31095                                       | 22.0 W | 4 1/4 | 25 3/8 | 6 1/2 |
|                                              |        |       |        | 4 3/8 |