

Application

A series of wall luminaires with shielded light distribution. The shape of the lantern is unmatched in its diversity. These luminaires are particularly suitable for illuminating areas directly below the mounting surface such as courtyards or alongside and above doors.

Materials

- Hand-blown three-ply opal glass
- 99.9% pure copper
- High-strength, free machining C38500 brass
- Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 44

Weight: 4.9 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage6.3W
- System wattage8.6W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens286lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Natural copper. Time and weather factors will create the natural patina of copper.

Type:


BEGA Product:

Project:

Modified:

Available options

DALI-2 Enabled for DALI control system



Copper wall luminaire · Unshielded				
	LED	A	B	C
B31171	6.3W	9 1/4	8 1/4	14 1/2
				4 3/8