

Application

Pillar luminaire with partially shielded light distribution. A combination of materials in perfect harmony with this classic luminaire shape.

Materials

Hand-blown three-ply opal glass
99.9% pure copper
Self-expanding sleeve anchors for pre-cast concrete

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 20.7 lbs.

Electrical

Operating voltage 120, 240 or 277VAC
Minimum start temperature -30° C
Maximum ambient temperature 90° C
LED module wattage 22.0 W
System wattage 25.5 W
Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 1342 lm
LED service life (L70) 60000 hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish


Natural cast bronze and copper. Time and weather factors will create the natural patina of bronze and copper.

Type:

BEGA Product:

Project:

Modified:



Cast bronze and copper pillar luminaire · Unshielded

	LED	A	B	C
B31437	22.0W	17 ³ / ₄	27 ⁵ / ₈	6 ⁷ / ₈

