

Application

Recessed wall luminaire with shielded light distribution that is ideal for glare-free illumination of ground surfaces, building entrances, stairs and footpaths. Separate installation housing allows for seamless coordination into construction and easy maintenance.

Materials

- Clear safety glass with white ceramic coating
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection
- Mechanically captive stainless steel fasteners
- Stainless steel screw clamps
- Composite installation housing
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 1.2 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	2.0W
System wattage	6.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	32 lm
LED service life (L70)	60000 hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- | | |
|---|---------------------------------------|
| ☐ Black (BLK) | ☐ Bronze (BRZ) |
| ☐ Silver (SLV) | ☐ White (WHT) |
| ☐ Natural Bronze (NTB) | ☐ RAL: |
| ☐ CUS: | |

Type:

BEGA Product:

Project:


Modified:

Available options

- | | |
|---------------------------------|---------------------------------|
| ☐ AMB | Amber LED |
| ☐ CUS | Custom finish |
| ☐ DALI-2 | Enabled for DALI control system |
| ☐ FSC | Fusing |
| ☐ MGU | Marine grade undercoat |
| ☐ NTB | Natural bronze (premium finish) |
| ☐ RAL | RAL Classic, matte finish |

Included (available for pre-shipment)

- ☐ BB24063 Installation housing



Recessed wall luminaire · Shielded				
	LED	A	B	C
B33017	2.0W	6 ⁵ / ₈	2 ³ / ₄	5

