

Application

Recessed wall luminaires with asymmetric light distribution ideal for the glare-free illumination of ground surfaces, building entrances, stairs and footpaths.

Materials

- Clear safety glass with optical texture
- Corrosion-resistant 304 grade stainless steel
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Aluminum installation housing
- Pure anodized aluminum reflector surface

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 2.2 lbs.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-30° C
- LED module wattage3.0W
- System wattage6.2W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens221 lm
- LED service life (L70)60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details


Finish

#4 brushed stainless steel. Custom colors are not available.

Type:
BEGA Product:
Project:
Modified:

Available options
DALI-2 Enabled for DALI control system

Included (available for pre-shipment)
BB3020LED Installation housing



Recessed wall luminaire · Asymmetric				
		LED	A	B
B33020	ADA	3.0W	6	4 ³ / ₄

