

Application

Recessed wall luminaire with directed light ideal for the illumination of wide ground surfaces, stairs and footpaths. Separate installation housing allows for seamless coordination into construction and easy maintenance.

Materials

BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 1.2 lbs.

Electrical

|                           |                |
|---------------------------|----------------|
| Operating voltage         | 120-277VAC     |
| Minimum start temperature | -40° C         |
| LED module wattage        | 4.1 W          |
| System wattage            | 6.0 W          |
| Controllability           | 0-10V dimmable |
| Color rendering index     | Ra > 80        |
| Luminaire lumens          | 301 lm         |
| LED service life (L70)    | 60000hrs       |

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- |                                               |                                       |
|-----------------------------------------------|---------------------------------------|
| <input type="checkbox"/> Black (BLK)          | <input type="checkbox"/> Bronze (BRZ) |
| <input type="checkbox"/> Silver (SLV)         | <input type="checkbox"/> White (WHT)  |
| <input type="checkbox"/> Natural Bronze (NTB) | <input type="checkbox"/> RAL:         |
| <input type="checkbox"/> CUS:                 |                                       |

Type:

BEGA Product:

Project:


Modified:

Available options

- |                              |                                 |
|------------------------------|---------------------------------|
| <input type="checkbox"/> CUS | Custom finish                   |
| <input type="checkbox"/> FSC | Fusing                          |
| <input type="checkbox"/> MGU | Marine grade undercoat          |
| <input type="checkbox"/> NTB | Natural bronze (premium finish) |
| <input type="checkbox"/> RAL | RAL Classic, matte finish       |

Included (available for pre-shipment)

- |                                  |                      |
|----------------------------------|----------------------|
| <input type="checkbox"/> BB24063 | Installation housing |
|----------------------------------|----------------------|



| Recessed wall luminaire · Directed light |       |                               |                               |   |
|------------------------------------------|-------|-------------------------------|-------------------------------|---|
|                                          | LED   | A                             | B                             | C |
| B33023                                   | 4.1 W | 6 <sup>5</sup> / <sub>8</sub> | 2 <sup>3</sup> / <sub>4</sub> | 5 |

