

Application

Recessed wall luminaire with asymmetric light distribution that is ideal for the illumination of ground surfaces, building entrances, stairs and footpaths. Separate installation housing allows for seamless coordination into construction and easy maintenance.

Materials

BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection
Composite installation housing
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 6.2 lbs.

Electrical

Operating voltage 120-277V AC
Minimum start temperature -40° C
LED module wattage 20.5 W
System wattage 25.0 W
Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 1869 lm
LED service life (L70) 60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
Natural Bronze (NTB) RAL:
CUS:

Type:

BEGA Product:

Project:


Modified:

Available options

CUS Custom finish
FSC Fusing
MGU Marine grade undercoat
NTB Natural bronze (premium finish)
RAL RAL Classic, matte finish

Included (available for pre-shipment)

BB24062 Installation housing



Recessed wall luminaire · Directed light				
	LED	A	B	C
B33060	20.5 W	20 1/2	5	5 1/2

