

Application

This unshielded luminaire is made of stainless steel and hand-blown, three-ply opal glass. Arranged individually or in groups, it is a great design element for a host of lighting applications.

Materials

- Hand-blown three-ply opal glass
- 316 grade stainless steel
- High temperature silicone gasket
- Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 64

Weight: 3.5 lbs.

Electrical

- | | |
|---------------------------|----------------|
| Operating voltage | 120-277VAC |
| Minimum start temperature | -30° C |
| LED module wattage | 5.9W |
| System wattage | 10.0W |
| Controllability | 0-10V dimmable |
| Color rendering index | Ra > 80 |
| Luminaire lumens | 761 lm |
| LED service life (L70) | 60000hrs |

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:
BEGA Product:
Project:
Modified:

Available options
DALI-2 Enabled for DALI control system
FSC Fusing



Wall luminaire · Unshielded			
	LED	A	B
B33150	5.9W	5 1/8	10

