

Application

Recessed wall luminaire with unshielded light distribution for the illumination of ground surfaces, building entrances, stairs and footpaths. Separate installation housing allows for seamless coordination into construction and easy maintenance.

Materials

Clear safety glass with white ceramic coating
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection
Stainless steel screw clamps
Composite installation housing

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 4.4 lbs.

Electrical

Operating voltage120-277V AC
Minimum start temperature-30° C
LED module wattage12.3 W
System wattage15.0 W
Controllability0-10V dimmable
Color rendering indexRa > 80
Luminaire lumens907 lm
LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- Natural Bronze (NTB)
- CUS:
- Bronze (BRZ)
- White (WHT)
- RAL:

Type:

BEGA Product:

Project:


Modified:

Available options

- CUSCustom finish
- DALI-2Enabled for DALI control system
- FSCFusing
- MGUMarine grade undercoat
- NTBNatural bronze (premium finish)
- RALRAL Classic, matte finish

Included (available for pre-shipment)

- BB24060Installation housing



Recessed wall luminaire · Unshielded				
	LED	A	B	C
B33155	12.3W	13	5	5 1/2