

Application

Recessed wall luminaire with unshielded light to be used as location luminaires for means of way finding. Separate installation housing allows for seamless coordination into construction and easy maintenance.

Materials

Clear safety glass with white ceramic coating
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection
Stainless steel screw clamps
Composite installation housing

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 6.2 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	9.8W
System wattage	13.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	938lm
LED service life (L70)	60000hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:
BEGA Product:
Project:
Modified:

Available options

CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL Classic, matte finish

Included (available for pre-shipment)

BB24062	Installation housing
---------	----------------------



Recessed wall luminaire · Location luminaire				
	LED	A	B	C
B33158	9.8W	20 1/2	5	5 1/2

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805)684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2026 Updated 08/21/26

