

Application

Recessed wall luminaire with unshielded light distribution for the illumination of ground surfaces, building entrances, stairs and footpaths. Separate installation housing allows for seamless coordination into construction and easy maintenance.

Materials

- Clear safety glass with white ceramic coating
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection
- Mechanically captive stainless steel fasteners
- Stainless steel screw clamps
- Composite installation housing

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 1.8 lbs.

Electrical

|                           |                                |
|---------------------------|--------------------------------|
| Operating voltage         | 120-277VAC                     |
| Minimum start temperature | -30° C                         |
| LED module wattage        | 5.8W                           |
| System wattage            | 9.0W                           |
| Controllability           | 0-10V, TRIAC, and ELV dimmable |
| Color rendering index     | Ra > 80                        |
| Luminaire lumens          | 516lm                          |
| LED service life (L70)    | 60000hrs                       |

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

|                      |              |
|----------------------|--------------|
| Black (BLK)          | Bronze (BRZ) |
| Silver (SLV)         | White (WHT)  |
| Natural Bronze (NTB) | RAL:         |
| CUS:                 |              |

Type:

BEGA Product:

Project:

Modified:

Available options

|     |                                 |
|-----|---------------------------------|
| CUS | Custom finish                   |
| FSC | Fusing                          |
| MGU | Marine grade undercoat          |
| NTB | Natural bronze (premium finish) |
| RAL | RAL Classic, matte finish       |

Included (available for pre-shipment)

|         |                      |
|---------|----------------------|
| BB24064 | Installation housing |
|---------|----------------------|



| Recessed wall luminaire · Unshielded |      |        |       |   |
|--------------------------------------|------|--------|-------|---|
|                                      | LED  | A      | B     | C |
| B33165                               | 5.8W | 10 1/8 | 2 3/4 | 5 |

