Type:
BEGA Product:
Project:
Modified:

**Application**
This wall luminaire is ideal for downward lighting in exterior or interior spaces. Arranged individually or in groups, this is a great design element for a host of lighting applications.

**Materials**
Clear safety glass with white ceramic coating
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Mechanically captive stainless steel fasteners
Silicone applied robotically to casting, plasma treated for increased adhesion

**NRTL** listed to North American Standards, suitable for wet locations
Protection class IP 64

**Weight:** 2.2 lbs.

**Electrical**

| | |
|---|---|
| Operating voltage | 120-277V AC |
| Minimum start temperature | -30° C |
| LED module wattage | 3.9 W |
| System wattage | 6.0 W |
| Controllability | 0-10V dimmable |
| Color rendering index | Ra > 80 |
| Luminaire lumens | 184 lm |
| LED service life (L70) | 60000 hrs |

**LED color temperature**
☐ 4000K (K4)
☐ 3500K (K35)
☐ 3000K (K3)
☐ 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.


**Available colors**
☐ Black (BLK)
☐ Silver (SLV)
☐ Natural Bronze (NTB)
☐ CUS:
☐ Bronze (BRZ)
☐ White (WHT)
☐ RAL:

**Available options**

| | |
|---|---|
| ☐ CUS | Custom finish |
| ☐ DALI-2 | Enabled for DALI control system |
| ☐ MGU | Marine grade undercoat |
| ☐ NTB | Natural bronze (premium finish) |
| ☐ RAL | RAL Classic, matte finish |

**Included (available for pre-shipment)**

| | |
|---|---|
| ☐ B19545 | Narrow opening wiring box |






**Wall luminaire** · Light emission on one side

| | LED | A | B | C |
|---|---|---|---|---|
| **B33319** | 3.9 W | $7^{7}/_{8}$ | $2^{1}/_{8}$ | $4^{3}/_{4}$ |

**BEGA** 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2026