

Application

This wall luminaire has a shielded light source with output in two directions. It is ideal for upward and downward lighting effects for interior and exterior locations. Arranged individually or in groups, this is a great design element for a host of lighting applications.

Materials

Pressed crystal glass with white ceramic coating on one side  
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners  
Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 9.5 lbs.

Electrical

|                           |                    |
|---------------------------|--------------------|
| Operating voltage         | 120, 240 or 277VAC |
| Minimum start temperature | -30° C             |
| LED module wattage        | 11.8 W             |
| System wattage            | 14.0 W             |
| Controllability           | 0-10V dimmable     |
| Color rendering index     | Ra > 80            |
| Luminaire lumens          | 846 lm             |
| LED service life (L70)    | 60000 hrs          |

LED color temperature

4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.


Available colors

|                      |              |
|----------------------|--------------|
| Black (BLK)          | Bronze (BRZ) |
| Silver (SLV)         | White (WHT)  |
| Natural Bronze (NTB) | RAL:         |
| CUS:                 |              |

Type:  
BEGA Product:  
Project:  
Modified:

Available options

|     |                                 |
|-----|---------------------------------|
| CUS | Custom finish                   |
| MGU | Marine grade undercoat          |
| NTB | Natural bronze (premium finish) |
| RAL | RAL Classic, matte finish       |



| Wall luminaire · Light emission on two sides |        |                                |                               |                               |
|----------------------------------------------|--------|--------------------------------|-------------------------------|-------------------------------|
|                                              | LED    | A                              | B                             | C                             |
| B33344                                       | 11.8 W | 13 <sup>7</sup> / <sub>8</sub> | 5 <sup>1</sup> / <sub>2</sub> | 7 <sup>3</sup> / <sub>8</sub> |

