

Application

This wall luminaire with a wide spread light distribution can be used to illuminate ground surfaces along walls. Able to be installed in either direction for uplight or downlight applications.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Silicone applied robotically to casting, plasma treated for increased adhesion
- Galvanized zinc-plated mounting bracket
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 11.0lbs.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-40° C
- LED module wattage26.6W
- System wattage32.0W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens3676 lm
- LED service life (L70)60000hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- ☐ Black (BLK)
- ☐ Silver (SLV)
- ☐ Natural Bronze (NTB)
- ☐ CUS:
- ☐ Bronze (BRZ)
- ☐ White (WHT)
- ☐ RAL:

Type:


BEGA Product:

Project:

Modified:

Available options

- ☐ CUSCustom finish
- ☐ FSCFusing
- ☐ MGUMarine grade undercoat
- ☐ NTBNatural bronze (premium finish)
- ☐ RALRAL Classic, matte finish
- ☐ SRGSurge protection



Wall washer · Lateral throw				
	LED	A	B	C
B33378	26.6W	12 1/2	5	8 5/8

