

Application

This wall luminaire with an asymmetric light distribution can be used to illuminate ceiling or ground surfaces in front of the mounting surface. Able to be installed in either direction for uplight or downlight applications.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Silicone applied robotically to casting, plasma treated for increased adhesion
- Galvanized zinc-plated mounting bracket
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 11.0lbs.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-40° C
- LED module wattage29.5W
- System wattage36.0W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens4549lm
- LED service life (L70)60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- |                      |              |
|----------------------|--------------|
| Black (BLK)          | Bronze (BRZ) |
| Silver (SLV)         | White (WHT)  |
| Natural Bronze (NTB) | RAL:         |
| CUS:                 |              |

Type:


BEGA Product:

Project:

Modified:

Available options

- |     |                                 |
|-----|---------------------------------|
| CUS | Custom finish                   |
| FSC | Fusing                          |
| MGU | Marine grade undercoat          |
| NTB | Natural bronze (premium finish) |
| RAL | RAL Classic, matte finish       |



Wall washer · Asymmetric

|        | LED   | A                              | B | C                             |
|--------|-------|--------------------------------|---|-------------------------------|
| B33386 | 29.5W | 12 <sup>1</sup> / <sub>2</sub> | 5 | 8 <sup>5</sup> / <sub>8</sub> |

